





Soft Tissue Injury Prevention Tool

Tip Sheets Trade: Carpenters/Laborers	
Job Task: Formwork - [General Tasks Dismantle steel shoring 1 frame at a time. Then stack 2 frames on top using forklift or crane to un-stack frames.	Dismantling & Removing Steel Shoring Common Tools Hammer Tool Belt
 Potential Risk Factors Risk Factors can lead to increased risk for Work Related Musculoskeletal Disorders (WMSD's) Working with Hands Overhead or Elbows Above Shoulders Moderate Risk when manually lowering shoring components down to ground worker during dismantling process. Moderate Risk with frequent forward back bending for extended periods when manually lowering shoring components down to ground worker during dismantling process. Moderate Risk with frequent forward back bending for extended periods when manually lowering shoring components down to ground worker during dismantling process. Moderate Risk when frequently lifting end frames, scaffold planks and extension frames for extended periods of time, particularly when lowering to ground worker, while standing on second frame level. 	 Possible Solutions Awkward Posture & Lifting Solutions: Store all materials above ground on material handling carts or stacked pallets for easier lifting and handling. Move all components to specific work location using a forklift or pallet jacks. Evaluate using forklift or scissor lift to lower all shoring components to ground level as part of dismantling process. Rotate from ground level to above ground shoring dismantling tasks every 2-4 hours. Potential Benefits Increases productivity. Increases blood flow and reduce muscle tension. Reduces strain on hand and arm muscles. Reduces awkward work postures and minimize lifting requirements.
 Feasibility Engineer Control Administrative Control Work Practice Control Estimated Cost of Intervention None 	